

Features

- Noise Figure ≤ 9.0 dB
- Unconditionally Stable at all temperatures
- Internally Regulated DC Voltage
- 50 Ohm Matched Input/Output
- Field Replaceable 2.4mm V connectors
- Excellent Group Delay and Phase Linearity
- 0.009 inches diameter RF In/Out feed through
- Operating Temp. -55 C to +85 C
- 3 Year Warranty

Options

- **Optimized Performance over Selected Bandwidth**
- Internally DC Block Input (Output DC Block Standard)
- Hermetically Sealed Package
- Improved Gain Flatness
- Improved IN and OUT VSWR
- Gain and Phase matching
- Lower Noise Figure




Specifications (23 °C)

Parameter	Min	Typ	Max	Units
Frequency Range	10	-	50	GHz
Noise Figure*	-	8.0	9.0	dB
Gain	18	20	-	dB
Gain Flatness (+/-)	-	± 2.0	± 2.5	dB
P1 Output Power	+8	+9	-	dBm
Input VSWR	-	2.5:1	2.7:1	
Output VSWR	-	2.5:1	2.7:1	
Operating Temperature	-55	-	+85	°C
Non-Operating Temp Range	-65	-	+125	°C
RF Input Power (no-damage)	-	-	+13	dBm
Humidity (non-condensing)	-	-	95	%
Voltage	+12	+12	+15	VDC
Current	-	245		mA
Input Impedance	50			Ohms
RF Connector	2.4mm - Female			
Dimensions	29.9 x 18.7 x 7.6			mm

* Noise Source used for measurement from 10GHz to 50 GHz is HP346C-K01.
 NF Uncertainty (approx. 0.3 dB). 0.2 dB due to ENR of HP 346C-K01, and 0.1 dB due to the gain modulation of the unit caused by the HP 346C-K01 source impedance change in the ON and OFF state.

Typical Data






Approx. Actual Size



Mounting Drawing



Drop In

