

Features

- **Noise Figure: 1.5 dB (typ)**
- Unconditionally Stable at all temperatures
- Internally Regulated DC Voltage
- 50 Ohm Matched Input/Output
- Field Replaceable 3.5mm SMA connectors
- Excellent Group Delay and Phase Linearity
- 0.009 inches diameter RF In/Out feed through
- Operating Temp. -55 C to +85 C
- 3 Year Warranty

Options

- **Optimized Performance over Selected Bandwidth**
- Internally DC Block Input (Output DC Block Standard)
- Hermetically Sealed Package
- Improved Gain Flatness
- Improved IN and OUT VSWR
- Gain and Phase matching
- Lower Noise Figure





Specifications (23 °C)

Parameter	Min	Typ	Max	Units
Frequency Range	17.7	-	26	GHz
Noise Figure*	-	1.5	1.6	dB
Gain	40	41	-	dB
Gain Flatness (+/-)	-	± 1.5	± 1.8	dB
P1 Output Power	+10	+12	-	dBm
Input VSWR	-	-	2.0:1	
Output VSWR	-	-	2.0:1	
Operating Temperature	-55	-	+85	°C
Non-Operating Temp Range	-65	-	+85	°C
RF Input Power (no-damage)	-	-	+13	dBm
Humidity (non-condensing)	-	-	95	%
Voltage	+8	-	+15	VDC
Current	-	150		mA
Input Impedance	50			Ohms
RF Connector	3.5mm SMA - Female			
Dimensions	29.9 x 18.7 x 7.6			mm

* Noise Source used for measurement from 0.01 to 26.5 GHz is HP346C .
NF Uncertainty (approx. 0. 1dB). 0.05 dB due to ENR of HP 346C; and 0.05 dB, due to the gain modulation of the unit, caused by the HP 346C source impedance change in the ON and OFF state.

Typical Data



[illegible]

Technical drawing of a Flat Filler, #303, showing dimensions and material specifications. The drawing includes a callout box with the text: 0.90LNM X .160" Flat Filler #303. Below this, it reads: JI MORRIS PROD. # NAS72ICE90-160. The drawing shows a rectangular block with four threaded holes. Dimensions are given as follows: .309 TYP (width), .315 TYP (length), .039 TYP (hole diameter), and .058 TYP (hole depth). A curved arrow indicates a 90-degree angle.